

HD119LD



Longer decap time and higher density

HD119LD is a water based ink for HP thermal inkjet. The most remarkable advantages are longer decap time and extra high density even at low resolution.

Features

- Dye and pigment hybrid colorant.
- Higher density and longer Decap time compared with comparable inks.
- High water resistance and lightfastness.
- Suitable for porous & semi-porous media.
- No heater required.
- Compliant with RoHS. PFAS Free.

Suggested substrates

Carton

Paper

Wood

Specification

Cartridge	HP 45ai (1/2")
Color	Black ●
Ink grade	Aqueous
Parameters	10.8V, 2.6μs
Pulse warming	Off
Shelf life	12 months from fill date
Storage temp.	15-35°C
Max frequency	12kHz

Remarks

- Refer to SDS before use for safe handling.
- Before use, wipe the printhead gently with a dry lint-free cloth or a cloth with deionized water.
- After use, seal the printhead with the originally attached cartridge clip and store the cartridge with the position of its printhead UP until next use.



300x300 Paper



www.linkedin.com



www.general.co.jp

- All technical information here is based on our laboratory evaluation and can be varied by real condition. Not always guaranteed.
- Conducting print test under user's real use condition is recommended to avoid any unexpected issues.
- The contents are subject to change without notice, so please contact us for the latest information.
- The image is for reference only. The color or quality may differ from the actual product.

