

HD119LD



Longer decap time and higher density

HD119LD is a water-based ink for HP TIJ 2.5. Its most notable advantages are longer decap time and extra-high density, even at low resolutions.

Features

- Hybrid dye- and pigment-based ink
- Higher density and longer decap time compared with conventional inks
- High water resistance and light fastness
- Suitable for porous and semi-porous media
- No heater required
- RoHS compliant; PFAS-free

Specifications

Cartridge	HP 45si (0.5")
Color	Black ●
Ink grade	Aqueous
Parameters	10.8V, 2.6μs
Pulse warming	Off
Shelf life	12 months from fill date
Operating / Storage temp.	15-35°C
Max frequency	12kHz

Suggested substrates

Carton

Paper

Wood

Handling & Usage Notes

- Refer to the SDS before use for safe handling.
- Before use, gently wipe the printhead with a dry, lint-free cloth or a lint-free cloth with deionized water.
- After use, seal the printhead with the originally attached cartridge clip and store the cartridge with the printhead facing upward until the next use.

2.0mm : ABCDEFGHI12345678
2.5mm : ABCDEF123456
3.0mm : ABCD12345



300x300 Paper



www.linkedin.com



www.general.co.jp

- All technical information provided herein is based on our laboratory evaluations and may vary depending on actual operating conditions. Performance is not guaranteed under all conditions.
- Conducting print tests under actual operating conditions is recommended to avoid unexpected issues.
- Specifications and contents are subject to change without notice. Please contact us for the latest information.
- Images are for reference only. Actual color and print quality may differ from the product shown.

Copyright©2026 General Co., Ltd. All Right Reserved.



Ink by GENERAL CO., LTD.