

IQ801



Low smudging during heat sealing and fast drying time

IQ801 is a unique solvent-based black ink designed for heat resistance, minimizing smudging and offsetting during heat-sealing processes. It is ideal for marking on packages sealed with heat sealers.

Features

- Reduced smudging and offsetting during heat sealing
- Fast drying time
- Compliant with RoHS; PFAS-free

Suitable substrates

OPP	PP	PET	PE
PVC	Rubber	Glass	AL
Coated-paper	Carton	Paper	Wood

Specifications

Cartridge	HP 45si (0.5")
Color	Black ●
Ink grade	Solvent
Parameters	9.6V, 1.6μs
Pulse warming	Off
Shelf life	9 months from fill date
Operating / Storage temp.	15-35°C
Max frequency	12kHz

Handling & Usage Notes

- Refer to the SDS before use to ensure safe handling.
- Before use, wipe the printhead gently with a dry lint-free cloth.
- After use, cover the printhead with the original cartridge clip and store the cartridge with the printhead facing up until next use.

2.0mm : ABCDEFGHI12345678
2.5mm : ABCDEF123456
3.0mm : ABCD12345



300x300 Cast-coated paper



www.linkedin.com



www.general.co.jp

- All technical information provided herein is based on our laboratory evaluations and may vary depending on actual operating conditions. Performance is not guaranteed under all conditions.
- Conducting print tests under actual operating conditions is recommended to avoid unexpected issues.
- Specifications and contents are subject to change without notice. Please contact us for the latest information.
- Images are for reference only. Actual color and print quality may differ from the product shown.

Copyright©2026 General Co., Ltd. All Right Reserved.



Ink by GENERAL CO., LTD.