

IQ133



Transparent color for over / under coating

IQ133 is a UV-LED curable clear ink for over or under coating. As over-coating ink, this prevents the other ink's print from being damaged. As under-coating ink, this helps the other ink to increase adhesion to substrate.

Features

- Useful as over / under coating ink.
- Useful as decorative ink .
- UV-LED lamp is required to stick on non-porous substrates.
- Compliant with RoHS. PFAS Free.

Specification

Cartridge	HP 45si (1/2")
Color	Clear ○
Ink grade	UV
Parameters	9.2V, 2.1μs
Pulse warming	Off
Shelf life	5 months from fill date
Storage temp.	15-35°C
Max frequency	12kHz

Suggested substrates

OPP	PP	PET	PE
PVC	Rubber	Glass	AL
Coated paper	Carton	Paper	Wood

Remarks

- Refer to SDS before use for safe handling.
- Before use, wipe the printhead gently with a dry lint-free cloth.
- Recommended lamp condition :
 - $\geq 8W$ 385nm
 - 2mm distance between lamp and media
 - Expose light 2-5 sec after printing**This can be varied depending on condition.*
- After use, seal the printhead with the originally attached cartridge clip and store the cartridge with the position of its printhead UP until next use. Keep the cartridge in light proof package is recommended to avoid clogging.



300x600 PVC



www.linkedin.com



www.general.co.jp

- All technical information here is based on our laboratory evaluation and can be varied by real condition. Not always guaranteed.
- Conducting print test under user's real use condition is recommended to avoid any unexpected issues.
- The contents are subject to change without notice, so please contact us for the latest information.
- The image is for reference only. The color or quality may differ from the actual product.