

SDC220K(M) is designed for care labels. Due to improved sensitivity, high quality printing is possible at low energy levels. Excellent resistance to washing and dry cleaning, and can print on nylon taffeta, polyester satin, acetate satin, polyester taffeta etc.

RECOMMENDED APPLICATION



PRINT HEAD TYPE

FLAT EDGE

RECOMMENDED SUBSTRATES

Uncoated paper	—
Coated paper	★ ★
Gloss paper	★ ★
Synthetic paper	★ ★ ★ ★
Tag paper	★ ★
Various types of film	★ ★ ★ ★
PET label	★ ★ ★ ★ ★
Care label	★ ★ ★ ★ ★

RIBBON SPECIFICATION

Back coating	non-Silicon based
Film Thickness	4.5 ± 0.3μ
Ribbon Thickness	6.8 ± 0.5μ
Ink Type	RESIN
Ink Melting Point	80°C

TYPICAL COMPLIANCE

- REACH-SVHC Free : EU REACH Regulation(1907/2006) Substance of Very High Concern(SVHC)
- RoHS : RoHS Directive(2002/95/EC)Conformity
- Halogen Free : Chlorine Content : 900ppm or less Bromine Content : 900ppm or less Chlorine and Bromine Total Contents : 1500ppm or less
- TSCA : Premanufacture Notification(PMN) Conformity

GENERAL CO.,LTD. www.general.co.jp/english/

Tokyo Head Office: 1-3-6 Nishikanda, Chiyoda-ku, Tokyo 101-0065 Phone: +81-3-5283-8640


[China] Unit. C 3F, Zao-Fong Universe Building, No. 1800 Zhong Shan Xi Road, Shanghai, China Phone: +86 (0) 21 6440 1196

[Malaysia] Lot 4298-4300 Sg. Choh Industrial Area 48000 Rawang, Selangor, Malaysia Phone: +60-3-6099-9000

[USA] 601 N. Parkcenter Drive, Suite 106 Santa Ana, CA 92705 Phone: +1 657-236-7312

[Italy] Via Giacomo Leopardi, 29 20123 Milan Italy Phone: +39 2-4548-6203

SENSITIVITY



RESISTANCE

