

SD310 can print on a variety of media at low energy levels.

This ribbon provides excellent chemical resistance
and high quality printing on various media.

RECOMMENDED APPLICATION



Shipping labels



Inventory labels



General ticketing



Retail tag labels



Pharmaceutical labels



Medical use labels



Identification cards



Name printing



Care labels



Flexible packaging



Price tags



Laboratory labels

PRINT HEAD TYPE

FLAT

EDGE

RECOMMENDED SUBSTRATES

Uncoated paper	—
Coated paper	★ ★ ★
Gloss paper	★ ★ ★
Synthetic paper	★ ★ ★ ★ ★
Tag paper	★ ★ ★
Various types of film	★ ★ ★ ★
PET label	★ ★ ★ ★ ★
Care label	—
PVC label	★ ★ ★ ★ ★

RIBBON SPECIFICATION

Back coating	non-Silicon based
Film Thickness	4.5 ± 0.3μ
Ribbon Thickness	7.0 ± 0.5μ
Ink Type	RESIN
Ink Melting Point	80 °C

TYPICAL COMPLIANCE

- REACH-SVHC : EU REACH Regulation(1907/2006) Substance of Very High Concern(SVHC) Conformity
- RoHS : RoHS2 Directive(2011 / 65/EU)Conformity
- TSCA : All components listed in TSCA Inventory

GENERAL CO.,LTD. www.general.co.jp/english/

Tokyo Head Office: 1-3-6 Nishikanda, Chiyoda-ku, Tokyo 101-0065 Phone: +81-3-5283-8640



[China] Unit. C 3F, Zao-Fong Universe Building, No. 1800 Zhong Shan Xi Road, Shanghai, China Phone: +86 (0) 21 6440 1196

[Malaysia] Lot 4298-4300 Sg. Choh Industrial Area 48000 Rawang, Selangor, Malaysia Phone: +60-3-6099-9000

[USA] 601 N. Parkcenter Drive, Suite 106 Santa Ana, CA 92705 Phone: +1 657-236-7312

[Italy] Via Giacomo Leopardi, 29 20123 Milan Italy Phone: +39 2-4548-6203

SENSITIVITY



RESISTANCE

