

SDF400 is designed for near-edge type print heads.
This ribbon provides excellent scratch resistance
and high quality printing on a variety of films.

RECOMMENDED APPLICATION



Shipping labels



Inventory labels



General ticketing



Retail tag labels



Pharmaceutical labels



Medical use labels



Identification cards



Name printing



Care labels



Flexible packaging



Price tags



Laboratory labels

PRINT HEAD TYPE

FLAT EDGE

RECOMMENDED SUBSTRATES

Uncoated paper	★ ★ ★
Coated paper	★ ★ ★ ★ ★
Gloss paper	★ ★ ★ ★ ★
Synthetic paper	★ ★ ★ ★ ★
Tag paper	★ ★ ★
Various types of film	★ ★ ★ ★ ★
PET label	★ ★ ★ ★ ★
Care label	—

RIBBON SPECIFICATION

Back coating	Silicon based
Film Thickness	4.5 ± 0.3μ
Ribbon Thickness	7.7 ± 0.7μ
Ink Type	WAX/RESIN
Ink Melting Point	68 °C

TYPICAL COMPLIANCE

- REACH-SVHC Free : EU REACH Regulation(1907/2006) Substance of Very High Concern(SVHC)
- RoHS : RoHS Directive(2002/95/EC)Conformity
- Halogen Free : Chlorine Content : 900ppm or less Bromine Content : 900ppm or less Chlorine and Bromine Total Contents : 1500ppm or less
- TSCA : Premanufacture Notification(PMN) Conformity
- Food Contact : Compliant with the European Directive 1935/2004/EC

GENERAL CO., LTD. www.general.co.jp/english/

Tokyo Head Office: 1-3-6 Nishikanda, Chiyoda-ku, Tokyo 101-0065 Phone: +81-3-5283-8640



[China] Unit. C 3F, Zao-Fong Universe Building, No. 1800 Zhong Shan Xi Road, Shanghai, China Phone: +86 (0) 21 6440 1196

[Malaysia] Lot 4298-4300 Sg. Choh Industrial Area 48000 Rawang, Selangor, Malaysia Phone: +60-3-6099-9000





[USA] 601 N. Parkcenter Drive, Suite 106 Santa Ana, CA 92705 Phone: +1 657-236-7312

[Italy] Via Giacomo Leopardi, 29 20123 Milan Italy Phone: +39 2-4548-6203

SENSITIVITY



RESISTANCE



■ Evaluated by JIS L 00850 test method of dying fastness against Hotpressing.